

AP-2416 Specifications



| | |
|--------------------------------|--|
| Compression Format | Standard H.264 Baseline |
| Video Output | Composite: 1.0V p-p/75Ω, (2) BNC, (1) S-Video, (1) VGA |
| Video Input | Composite: 1.0V p-p/75Ω, (16) BNC |
| Display Resolution | PAL: 720x576; NTSC: 720x480 |
| Record Resolution | PAL: 352x288, 704x576; NTSC: 352x240, 704x480 |
| Display Frame Rate | PAL: 400FPS; NTSC: 480FPS |
| Record Frame Rate | PAL: 400FPS, 100FPS; NTSC: 480FPS, 120FPS |
| Audio Input | -8dB~ 22k, (16) RCA |
| Audio Output | -8Db~92dB, (1) RCA |
| Alarm Input | NO or NC 16CH |
| Alarm Output | 4CH |
| Record Mode | Manual, Sensor, Timer, Motion detection |
| Simplex/Duplex/Triplex | Pentaplex |
| Network Interface | RJ45 (LAN, Internet) |
| PTZ control | Yes |
| Communication interface | RS485, (2) USB2.0, (1) PS/2 |
| Hard disk info | (3) SATA + (1) DVD-RW or (4) SATA |
| Remote controller | Yes |
| Power supply | 100-230V |